



Specifications and technical data are subject to change without notice.

Please contact to confirm relevant information on ordering.

📍 No.18, Gutang Rd, Shanghai 201209, China

☎ +86 21 5032 0898

📠 +86 21 5032 0828

✉ info@ebasee.com

🌐 www.ebasee.com



Copy right reserved EBS.NO.2021001

EBASEE
Smart Living Green Ebasee



MODULAR TERMINAL



COMPANY PROFILE

As a leading supplier in the low voltage electrics industry, Shanghai Ebasee Electric Co., Ltd. products have been used for residential, commercial and industrial applications with its quality and service. EBASEE brand is recognized for its quality and reliability in an ever-increasing number of markets worldwide. So far EBASEE products have been approved by international labs including BV, TUV, Intertek, with KEMA, CB, SEMKO, RoHS, CE, and CCC etc.

With qualified raw materials and components supply, all products are manufactured by EBASEE's defined international specifications. We have 4 semi-auto production lines, up-to-date quality control facilities, well-trained and experienced workers. Moreover, with a technical R & D team and fully equipped in-house laboratory, EBASEE factory can carry out efficient new products development, daily production and QC.

EBASEE have a wide range of cooperations with world leading companies in new products development, OEM and ODM cooperation. Meanwhile, we process the idea of green and smart energy, working with universities such as Xi'an Jiao Tong University to get more intelligent and environmental electric solutions.


EBASEE focused on achieving growth through the success of worldwide partners. Guided by the philosophy of "market-oriented", powered by the idea of "Quick response and flexible supply", EBASEE support our worldwide partners to compete against established global players, to deliver the most systemetic and cost-effective products and service in the market.

"Smart life, Green EBASEE"



Quality is our culture!

PRODUCTION LINE








SMART LIVING GREEN EBASEE



INTERNATIONAL QUALITY CERTIFICATE

EBASEE products have been approved by international labs including BV, TUV, Intertek, with KEMA, CB, SEMKO, RoHS, CE, and CCC etc.



1.Function

- Suitable for industrial, commercial, high-rise and civil residences circuit protection.
- Overload& short circuit protection
 - Protect people against indirect contacts and additional protection against direct contacts.
 - Protect installations against fire hazard due to insulation faults.
 - Control electric circuits



2.Nomenclature

EBS 1BLE - 63 / 30

- Rated residual current(mA)
- Frame level
- Design code
- Company code



3.Specifications

Type	Standard		IEC/EN 61009-1
Electrical features	Poles	P	1P+N
	Type(wave form of the earth leakage sensed)		AC
	Thermo-magnetic release characteristic		B, C
	Rated current In	A	6, 10, 16, 20, 25, 32, 40, 50, 63
	Rated voltage Ue	V	240
	Rated sensitivity IΔn	A	0.03, 0.05, 0.1, 0.3
	Rated residual making and breaking capacity IΔm	A	500(In≤40A) 630(In>40A)
	Rated short-circuit capacity Icn	A	4500, 6000
	Break time under IΔn	s	≤0.1
	Rated frequency	Hz	50/60
	Rated impulse withstand voltage(1.2/50)Uimp	V	4000
	Dielectric test voltage at ind.Freq.for 1min	kV	2
	Insulation voltage Ui	V	250
Mechanical features	Pollution degree		2
	Electrical life	t	4000
	Mechanical life	t	10000
	Contact position indicator		Yes
	Protection degree		IP20
	Ambient temperature(with daily average≤35℃)	℃	-5~+40
	Storage temperature	℃	-25~+70
Installation	Terminal connection type		Cable/Pin-type busbar
	Terminal size top/bottom for cable	mm²	25
		AWG	18-3
	Terminal size top/bottom for busbar	mm²	25
		AWG	18-3
	Tightening torque	N*m	2
		In-lbs	18
	Mounting		On DIN rail EN60715(35mm)by means of fast clip device
	Connection		From top

4.Release

Item	Tripping Curve	Test current In(A)	Initial Status	Time limit for tripping or non-tripping	Expected result	Remarks
a	B/C	1.13In	Cold	t≤1h	Non-tripping	Current smoothly rises to specified value within 5s
b	B/C	1.45In	Following item a test	t<1h	Tripping	
c	B/C	2.55In	Cold	1s<t<60s(In≤32A) 1s<t<120s(In>32A)	Tripping	
d	B	3In	Cold	t≤0.1s	Non-tripping	Switch on the power supply by closing the auxiliary switch
	C	5In			Non-tripping	
e	B	5In	Cold	t<0.1s	Tripping	
	C	10In			Tripping	

Note: The term"cold "means that the test is carried out at a reference calibration temperature without load before the test.



5.Conductor

Copper cross-section(mm²)	Rated current In(A)
1	In≤6
1.5	6<In≤13
2.5	13<In≤20
4	20<In≤25
6	25<In≤32
10	32<In≤50
16	50<In≤63

M

6.Temperature Derating

The maximum permissible current in a circuit breaker depends on the ambient temperature where the circuit breaker is placed. Ambient temperature is the temperature inside the enclosure or switchboard in which the circuit breakers are installed. The reference temperature is 30℃.

When several simultaneously operating circuit breakers are mounted side by side in a small enclosure,the temperature rise inside the enclosure causes a reduction in current rating.
You must then assign the rating (already derated if necessary according to ambient temperature), a downrating factor of 0.8.

7.Order Note

Following items should be marked when ordering	Ordering sample
Product name, model & frame level	To order the EBS1BLE RCBO,frame level 63A,rated current is 20A,
Poles	tripping curve is C,rated residual current 30mA 4.5kA and quantity is
Tripping characteristic and rated current	100 pieces, should be marked:
Quantity	RCBO EBS1BLE-63/C20/30, 4.5kA 100pcs